

Silicon Varicap Diode

BB404B

43pF – 44.5pF

DATASHEET

OEM – ITT

Source:


ITT databook discrete semiconductors for surface mounting 1991

BB404

Tuner Diode


Si Epitaxial Planar Dual Capacitance Diode for tuning in the VHF range, especially in car receivers.

These diodes are delivered taped.
Details see "Taping".



Plastic Package JEDEC TO-236
23 A 3 according to DIN 41869

Weight approx. 0.01 g
Dimension in mm



Marking code

Type	Marking
BB404A	A4
BB404B	B4
BB404C	C4
BB404D	D4
BB404E	E4

Absolute Maximum Ratings

	Symbol	Value	Unit
Reverse Voltage	V_R	15	V
Junction Temperature	T_j	125	°C
Storage Temperature Range	T_S	-55 to +125	°C

BB404

Characteristics at $T_j = 25\text{ }^\circ\text{C}$

	Symbol	Min.	Typ.	Max.	Unit
Capacitance at $f = 1\text{ MHz}$, $V_R = 2\text{ V}$	Group A C_{tot}	42	–	47.5	pF
	B C_{tot}	42	–	43.5	pF
	C C_{tot}	43	–	44.5	pF
	D C_{tot}	44	–	45.5	pF
	E C_{tot}	45	–	46.5	pF
Effective Capacitance Ratio at $V_R = 2\text{ to }8\text{ V}$	$\frac{C_{tot}(2\text{ V})}{C_{tot}(8\text{ V})}$	1.65	–	1.75	–
Series Resistance at $f = 100\text{ MHz}$, $C_{ext} = 38\text{ pF}$	r_s	–	–	0.4	Ω
Leakage Current at $V_R = 10\text{ V}$	I_R	–	–	20	nA
Basic Tolerance ¹⁾ at $V_R = 2\text{ V}$	$ K $	–	–	1	%
¹⁾ Difference of capacitance values of the individual diodes in one package.					